

PRO-SET® LAM-251-HT Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 06/01/2015

Revision date: 10/06/2016

Version: LAM-251-HT-2016a

SECTION 1: Identification

Identification

Product form : Mixtures
Product name : PRO-SET® LAM-251-HT Hardener
Product code : LAM-251-HT, LAM-251-HT-1, LAM-251-HT-2, LAM-251-HT-3, LAM-251-HT-4, LAM-251-HT-5, LAM-251-HT-6.

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Curing agent for laminating epoxy resins

Details of the supplier of the safety data sheet

Manufacturer

Gougeon Brothers, Inc
100 Patterson Ave.
Bay City, MI 48706 - U.S.A.
T 888-377-6738 or 989-684-7286
www.prosetepoxy.com

Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300
CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Acute Tox. 4 (Oral)
Acute Tox. 3 (Dermal)
Acute Tox. 2 (Inhalation)
Skin Corr. 1A
Eye Dam. 1
Skin Sens. 1
Carc. 2
Aquatic Acute 2
Aquatic Chronic 2

Label elements

Hazard pictograms (GHS)



Signal word (GHS)

Danger

Hazard statements (GHS)

Harmful if swallowed. Toxic in contact with skin. Fatal if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing cancer. Toxic to aquatic life. Toxic to aquatic life with long lasting effects

Precautionary statements (GHS)

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust, fume, gas, mist, vapours, spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves, protective clothing, eye protection, face protection. In case of inadequate ventilation wear respiratory protection. If swallowed: rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Immediately call a poison center/doctor. If irritation or rash occurs: Get medical attention/advice. Take off immediately all contaminated clothing and wash it before reuse. Collect spillage. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

PRO-SET® LAM-251-HT Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Other hazards

No additional information available

Unknown acute toxicity

No additional information available

SECTION 3: Composition/information on ingredients

Substances

Not applicable

Mixtures

Name	Product identifier	%
Cyclohexanamine, 4,4'-methylenebis[2-methyl-	(CAS No) 6864-37-5	60 - 100
Isophorone diamine	(CAS No) 2855-13-2	10 - 30
1H-Imidazole, 2-ethyl-4-methyl-	(CAS No) 931-36-2	1 - 10
4-Methylimidazole	(CAS No) 822-36-6	0.1 - 1

The exact chemical identity and/or exact percentage (concentration) of each ingredient may be held as confidential business information (CBI). Any ingredient not disclosed in this section may have been determined not to be hazardous to health or the environment, or it may be present at a level below its disclosure threshold. Refer to Section 15 for additional information regarding this CBI claim.

SECTION 4: First aid measures

Description of first aid measures

- First-aid measures after inhalation** : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after skin contact** : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after eye contact** : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- First-aid measures after ingestion** : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation** : Fatal if inhaled. May cause respiratory tract irritation.
- Symptoms/injuries after skin contact** : Toxic in contact with skin. Causes severe burns. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction.
- Symptoms/injuries after eye contact** : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
- Symptoms/injuries after ingestion** : Harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause stomach distress, nausea or vomiting.

Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Foam. Carbon dioxide. Dry chemical.
- Unsuitable extinguishing media** : Do not use a heavy water stream.

Special hazards arising from the substance or mixture

- Fire hazard** : Products of combustion may include, and are not limited to: oxides of carbon, nitrogen oxides, amines, ammonia.
- Reactivity** : No dangerous reaction known under conditions of normal use.

Advice for firefighters

- Protection during firefighting** : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

PRO-SET® LAM-251-HT Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

For non-emergency personnel

No additional information available

For emergency responders

No additional information available

Environmental precautions

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). Do not absorb in sawdust, paper, cloth or other combustible absorbents.

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe dust, fume, gas, mist, vapours, spray. Do not swallow. Handle and open container with care. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. When mixed with epoxy resin this product causes an exothermic reaction, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapors that vary widely in composition and toxicity.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking. Contaminated work clothing should not be allowed out of the workplace.

Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in dry, cool, well-ventilated area. Protect from moisture. Storage temperature : 40°F (4°C) - 90°F (32°C).

SECTION 8: Exposure controls/personal protection

Control parameters

Cyclohexanamine, 4,4'-methylenebis[2-methyl- (6864-37-5)
Not applicable
Isophorone diamine (2855-13-2)
Not applicable
1H-Imidazole, 2-ethyl-4-methyl- (931-36-2)
Not applicable
4-Methylimidazole (822-36-6)
Not applicable

Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

PRO-SET® LAM-251-HT Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Amber
Odour	: Ammonia
Odour threshold	: No data available
pH	: 11 - 11.6 (estimated based on ingredient data)
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 300 °F (204°C) estimated based on similar product
Flash point	: > 200 °F (93°C) estimated based similar product
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not flammable
Vapour pressure	: < 1 mm Hg @ 20°C / 68°F (estimated based on ingredient data).
Relative vapour density at 20 °C	: No data available
Relative density	: 0.94
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 42.5 mm ² /s @ 22°C /72 °F
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Other information	
VOC content	: 0.01 g/l (0.00 lbs/gal)
Bulk density	: 7.83 lb/gal (0.94 kg/L)

SECTION 10: Stability and reactivity

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal storage conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use. A mass of more than one pound of product plus an epoxy resin will cause irreversible polymerization with significant heat buildup and pressure.
Conditions to avoid	: Heat. Incompatible materials.
Incompatible materials	: Acids. Oxidizing materials. Halogenated compounds. Sodium hypochlorite. Acid chlorides. Acid anhydrides. Nitrosating agents.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon, nitrogen oxides, amines, ammonia.

SECTION 11: Toxicological information

Information on toxicological effects

Cyclohexanamine, 4,4'-methylenebis[2-methyl- (6864-37-5)	
LD50 oral rat	320 - 460 mg/kg
LD50 dermal rabbit	> 200 mg/kg
LC50 inhalation rat	0.42 mg/l/4h

PRO-SET® LAM-251-HT Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Isophorone diamine (2855-13-2)	
LD50 oral rat	1030 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.01 mg/l/4h

1H-Imidazole, 2-ethyl-4-methyl- (931-36-2)	
LD50 oral rat	731 - 1000 mg/kg
LD50 dermal rabbit	> 400 mg/kg

4-Methylimidazole (822-36-6)	
LD50 oral rat	350 - 751 mg/kg
LD50 dermal rabbit	440 mg/kg

Acute toxicity (oral)	: Oral: Harmful if swallowed.
Acute toxicity (dermal)	: Dermal: Toxic in contact with skin.
Acute toxicity (inhalation)	: Inhalation: Fatal if inhaled.
Skin corrosion/irritation	: Causes severe skin burns
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.

4-Methylimidazole (822-36-6)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.

PRO-SET® LAM-251-HT Hardener	
Viscosity, kinematic (calculated value) (22 °C)	42.5 mm ² /s

Potential adverse human health effects and symptoms	: Fatal if inhaled. Toxic in contact with skin. Harmful if swallowed.
Symptoms/injuries after inhalation	: Fatal if inhaled. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Toxic in contact with skin. Causes severe burns. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/injuries after ingestion	: Harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause stomach distress, nausea or vomiting.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Cyclohexanamine, 4,4'-methylenebis[2-methyl- (6864-37-5)	
EC50 Daphnia 1	15.2 mg/l (Exposure time: 48 h - Species: Daphnia magna Straus)

Isophorone diamine (2855-13-2)	
EC50 Daphnia 1	14.6 - 21.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [semi-static])

4-Methylimidazole (822-36-6)	
EC50 Daphnia 1	180 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Persistence and degradability

PRO-SET® LAM-251-HT Hardener	
Persistence and degradability	Not established.

PRO-SET® LAM-251-HT Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Bioaccumulative potential

PRO-SET® LAM-251-HT Hardener	
Bioaccumulative potential	Not established.
Cyclohexanamine, 4,4'-methylenebis[2-methyl- (6864-37-5)	
Partition coefficient n-octanol/water	2.51 (at 25 °C)
Isophorone diamine (2855-13-2)	
Partition coefficient n-octanol/water	0.79 (at 23 °C)
4-Methylimidazole (822-36-6)	
Partition coefficient n-octanol/water	0.35 (at 25 °C)

Mobility in soil

PRO-SET® LAM-251-HT Hardener	
Ecology - soil	No additional information available.

Other adverse effects

Effect on the global warming : No known effects from this product.

Ingredient	CAS#	Ecotoxicity Classification Information
2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)	6864-37-5	Acute Aquatic Cat. 2; Chronic Aquatic Cat. 2
Isophoronediamine	2855-13-2	Acute Aquatic Cat. 3; Chronic Aquatic Cat. 3
2-ethyl-4-methylimidazole	931-36-2	Acute Aquatic Cat. 3; Chronic Aquatic Cat. 3
4-Methylimidazole	822-36-6	Not classified

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

Waste treatment methods

Product/Packaging disposal recommendations : Avoid release to the environment. This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT and TDG

UN-No. (DOT/TDG) : UN2922
Proper Shipping Name (DOT/TDG) : Corrosive liquids, toxic, n.o.s. (Cyclohexanamine, 4,4'-methylenebis[2-methyl-)
Class (DOT/TDG) : 8 (6.1)
Packing group (DOT/TDG) : II
Marine pollutant : No

Transport by sea

In accordance with IMDG

UN-No. (IMDG) : 2922
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, TOXIC, N.O.S. (Cyclohexanamine, 4,4'-methylenebis[2-methyl-)
Class (IMDG) : 8 (6.1)
Packing group (IMDG) : II
EmS Number : F-A, S-B
Marine pollutant : Yes

Transport by air

In accordance with IATA

UN-No. (IATA) : 2922
Proper Shipping Name (IATA) : Corrosive liquid, toxic, n.o.s. (Cyclohexanamine, 4,4'-methylenebis[2-methyl-)
Class (IATA) : 8 (6.1)
Packing group (IATA) : II
Marine pollutant : Yes

PRO-SET® LAM-251-HT Hardener

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

Canada WHMIS Confidential Business Information (CBI): The HMIRA number issued for this CBI claim is #10410. The date of filing is 2016-09-23

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm


4-Methylimidazole (822-36-6)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	29 µg/day

Isophorone diamine (2855-13-2)
U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Date of issue : 06/01/2015
Revision date : 10/06/2016
Other information : None.

NFPA health hazard : 3
NFPA fire hazard : 1
NFPA reactivity : 0



HMIS III Rating
Health : 3 Serious Hazard
Flammability : 1 Slight Hazard
Physical : 0 Minimal Hazard

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.