

SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:..... PRO-SET® LAM-251-HT Hardener
APPLICABLE PRODUCT CODES: LAM-251-HT, LAM-251-HT-1, LAM-251-HT-2, LAM-251-HT-3, LAM-251-HT-4, LAM-251-HT-5, LAM-251-HT-6.
CHEMICAL FAMILY:..... Polyamine-imidazole mixture.
INTENDED PRODUCT USES:..... Curing agent for laminating epoxy resins.
PRODUCT RESTRICTIONS: None identified.
SDS VERSION: LAM-251-HT-2016a

MANUFACTURER:
Gougeon Brothers, Inc.
100 Patterson Ave.
Bay City, MI 48706, U.S.A.
Phone: 888-377-6738 or 989-684-7286
www.prosetepoxy.com

EMERGENCY TELEPHONE NUMBERS (24 HRS):
Transportation
CHEMTREC: 800-424-9300 (U.S.)
703-527-3887 (International)
Non-transportation
Poison Hotline: 800-222-1222

2. HAZARDS IDENTIFICATION

Classification of Substance or Mixture

Acute toxicity, Oral, Category 4
Acute toxicity, Dermal, Category 3
Acute toxicity, Inhalation, Category 2
Skin corrosion/irritation, Category 1A
Skin sensitizer, Category 1
Eye damage/irritation, Category 1
Carcinogenicity, Category 2
Acute aquatic toxicity, Category 2
Chronic aquatic toxicity, Category 2

Label Elements

Hazard Pictogram(s):



Signal Word:
DANGER

Hazard Statements:

H302 Harmful if swallowed
H311 Toxic in contact with skin
H330 Fatal if inhaled
H314 Causes severe skin burns and eye damage
H317 May cause an allergic skin reaction
H351 Suspected of causing cancer
H411 Toxic to aquatic life with long lasting effects

Precautionary Statements:

Prevention

P201 Obtain special instructions before use
P202 Do not handle until all safety precautions have been read and understood
P260 Do not breathe dust/fume/gas/mist/vapors/spray
P264 Wash hands thoroughly after handling
P270 Do not eat, drink or smoke when using this product
P271 Use only outdoors or in a well-ventilated area
P272 Contaminated work clothing should not be allowed out of the workplace
P273 Avoid release to the environment
P280 Wear protective gloves/protective clothing/eye protection/face protection
P284 In case of inadequate ventilation wear respiratory protection

Response

P301 + P330 + 331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse or wash skin with soap and water (or shower).
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

PRO-SET® LAM-251-HT Hardener

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical attention

P310 Immediately call POISON CENTER or doctor.

P313 + P333 If irritation or rash occurs: Get medical attention/advice

P362 + P364 Take of contaminated clothing and wash it before reuse

P391 Collect spillage

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal

P501 Dispose of contents and container according to local, state, national and International regulations

Other Hazards

None known.

3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT NAME	CAS #	CONCENTRATION (%)
2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)	6864-37-5	60-100
Isophoronediamine	2855-13-2	10-30
2-ethyl-4-methylimidazole	931-36-2	1-10
4-Methylimidazole	822-36-6	0.1-1

The exact chemical identity and/or exact percentage (concentration) of each ingredient may be held as a trade secret. Ingredient ranges provided may represent actual concentration ranges. Any ingredient not disclosed may have been determined not to pose a hazard, or may only be present in concentrations that do not require disclosure. Refer to Section 15 for additional information regarding a WHMIS CBI claim.

4. FIRST AID MEASURES

FIRST AID FOR EYES:..... SYMPTOMS: Causes eye burns and eye damage. RESPONSE: Flush immediately with water for at least 15 minutes. Remove contact lenses if present and easy to do. Immediately call a POISON CONTROL CENTER or doctor.

FIRST AID FOR SKIN:..... SYMPTOMS: Toxic in contact with skin. Causes severe skin burns, redness and irritation. May cause allergic skin reaction and sensitization. RESPONSE: Immediately wash skin with soap and water. Immediately call a POISON CONTROL CENTER or doctor.

FIRST AID FOR INHALATION:..... SYMPTOMS: Fatal if inhaled. Can cause respiratory irritation, shortness of breath or cough. Effects can be immediate or delayed. In the case of inhalation of thermal decomposition products, the exposed person may need to be kept under medical surveillance for 48 hours. RESPONSE: Remove to fresh air if effects occur and keep comfortable for breathing. Immediately call a POISON CONTROL CENTER or doctor.

FIRST AID FOR INGESTION:..... SYMPTOMS: May cause gastrointestinal irritation or ulceration. May cause burns of the mouth and throat. If vomiting occurs, the head should be kept low to prevent vomitus from entering lungs. RESPONSE: Rinse mouth with water. DO NOT induce vomiting. If vomiting should occur, keep airway clear. Immediately call POISON CONTROL CENTER or doctor.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: SUITABLE: Foam, carbon dioxide (CO₂), dry chemical. NON-SUITABLE: Direct water stream.

FIRE AND EXPLOSION HAZARDS: During a fire, smoke may contain the original materials in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include, but are not limited to: oxides of nitrogen, carbon monoxide, carbon dioxide, volatile amines, ammonia. When mixed with sawdust, wood chips, or other cellulosic material, spontaneous combustion can occur under certain conditions. Heat is generated as the air oxidizes the amine. If the heat is not dissipated quickly enough, it can ignite the sawdust.

SPECIAL FIRE FIGHTING PROCEDURES: Use full-body protective gear and a self-contained breathing apparatus. Use of water may generate toxic aqueous solutions. Do not allow water run-off from fighting fire to enter drains or other water courses.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS AND PROTECTIVE EQUIPMENT: Keep unnecessary, untrained, and unprotected personnel from entering area. Use appropriate safety and personal protective equipment as indicated in Section 8.

PRO-SET® LAM-251-HT Hardener

MITIGATION AND CLEAN UP PROCEDURES: Stop leak without additional risk. Isolate area. Dike and absorb with inert material (e.g., sand, limestone powder) and collect in a suitable, closed container. Do not use sawdust, wood chips or other cellulosic materials to absorb the spill, as the possibility for spontaneous combustion exists. Warm, soapy water may be used to clean residual.

ENVIRONMENTAL PRECAUTIONS:..... Prevent from entering into soil, ditches, sewers, waterways and groundwater. See Section 12 for environmental impact information.

7. HANDLING AND STORAGE

STORAGE TEMPERATURE (min./max.): 40°F (4°C) / 90°F (32°C).

STORAGE: Store in cool, dry place away from high temperatures and moisture. Store in a well-ventilated area, away from incompatible materials listed in Section 10. Keep container tightly closed. Store in a secure location with restricted access or store locked up.

HANDLING PRECAUTIONS: Use only with adequate ventilation or respiratory protection. Use PPE as described in Section 8. Do not breathe vapors, aerosols or mists from material. Prevent all skin and eye contact. Wash thoroughly after handling. When mixed with epoxy resin this product causes an exothermic reaction, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapors that vary widely in composition and toxicity. Do not breathe vapors or fumes from uncontrolled exotherming masses.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION GUIDELINES: Chemical splash-proof goggles or face shield.

SKIN PROTECTION GUIDELINES: Wear liquid-proof, chemical resistant gloves (nitrile-butyl rubber, butyl rubber or ethyl vinyl alcohol laminate EVAL) and full body protective clothing. Consider the parameters specified by the glove manufacturer and check during use to ensure that gloves are still retaining their protective properties.

RESPIRATORY/VENTILATION GUIDELINES: Use with adequate general ventilation and/or local ventilation to keep exposures below established limits. When ventilation cannot be made adequate enough to keep exposures below established limits, use a NIOSH approved respirator with an organic vapor cartridge, organic vapor cartridge + P100, or a multi-contaminant cartridge, depending on specific workplace conditions. Consult with your respirator and cartridge supplier to ensure proper selection of respirator and cartridge based on ingredients listed in Section 3 and specific workplace conditions. Use and select a respirator according to the guidelines established in OSHA 1910.134 or other applicable respiratory protection standard.

ADDITIONAL PROTECTIVE MEASURES: Use where there is immediate access to safety shower and emergency eye wash. Wash thoroughly after use. Contact lens should not be worn when working with this material. Generally speaking, working cleanly and following basic precautionary measures will greatly minimize the potential for harmful exposure to this product under normal use conditions.

OCCUPATIONAL EXPOSURE LIMITS: Exposure limits may not be established for this product as a whole. For established exposure limits of specific ingredients in this product, or other available exposure limit information, refer to the table below.

Ingredient Name	CAS#	Exposure Limit Information
2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)	6864-37-5	No data available
Isophoronediamine	2855-13-2	No data available
2-ethyl-4-methylimidazole	931-36-2	No data available
4-Methylimidazole	822-36-6	No data available

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM: Liquid.
COLOR: Amber
ODOR: Ammonia-like
ODOR THRESHOLD: No data available
pH: 11.0 – 11.6 (estimated based on ingredient data).
MELTING POINT / FREEZING POINT No data.
BOILING POINT (760mm/Hg): > 300°F (204°C) estimated based on similar product.
FLASH POINT: Estimated > 200°F (93°C) estimated based similar product.
AUTO IGNITION TEMPERATURE No data.
LOWER EXPLOSIVE LIMIT (LEL) No data.
UPPER EXPLOSIVE LIMIT (UEL) No data.
VAPOR PRESSURE < 1 mmHg @ 20°C (estimated based on ingredient data).
SPECIFIC GRAVITY/DENSITY (water = 1) 0.94
BULK DENSITY 7.83 lbs./gal. (0.94 kg/L)
VAPOR DENSITY (air = 1) No data.
EVAPORATION RATE (Butyl Acetate = 1) No data.
WATER SOLUBILITY (% BY WT.) No data.
PARTITION COEFFICIENT, n-OCTANOL/WATER (log Pow) No data.
KINEMATIC VISCOSITY: 42.5 (mm²/s @ 22°C)
DECOMPOSITION TEMPERATURE: No data available.
% VOLATILE BY WEIGHT: ASTM 2369-07 was used to determine the Volatile Matter Content of mixed epoxy resin and hardener. The combined VOC content for the resin and hardener system is listed below.

PRO-SET® LAM-251-HT Hardener

Resin/Hardener	VOC Content	
	(g/L)	(lb/gal)
LAM-151-HT / LAM-251-HT	0.01	0.00

10. STABILITY AND REACTIVITY

STABILITY: Product is stable at normal temperatures and pressures.

REACTIVITY / HAZARDOUS REACTIONS: Product will not react by itself. A mass of more than one pound of product plus an epoxy resin will cause irreversible polymerization with significant heat buildup and pressure.

INCOMPATIBILITIES: Strong exothermic reaction with acids. Avoid organic and mineral acids, oxidizing materials, halogenated organic compounds (e.g., methylene chloride), nitro sating agents, sodium hypochlorite, acid chlorides and acid anhydrides. External heating or self-heating could result in rapid temperature increase and pressure build up. If such a condition were to occur in a drum, the drum could expand and rupture violently. Can have corrosive effects on some metals.

CONDITIONS TO AVOID: Avoid excessive heat.

DECOMPOSITION PRODUCTS: Very toxic fumes and gases when burned or otherwise heated to decomposition. Decomposition products may include, but not limited to: oxides of nitrogen, volatile amines, ammonia.

11. TOXICOLOGICAL INFORMATION

Ingredient Name	CAS#	LD ₅₀ Oral	LD ₅₀ Dermal	LC ₅₀ Inhalation
2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)	6864-37-5	320-460 mg/kg	>200 mg/kg	0.42 mg/L; 4h (aerosol/mist)
Isophoronediamine	2855-13-2	1030 mg/kg	>2000	>5.01 mg/l 4h mist
2-ethyl-4-methylimidazole	931-36-2	731-1000 mg/kg	>400 mg/kg	No data
4-Methylimidazole	822-36-6	350-751 mg/kg	440 mg/kg	No data

ACUTE TOXICITY: No specific toxicity data exists for this mixture. Classification is based on acute toxicity estimation methods using ingredient data.
 Oral: Category 4. Harmful if swallowed. May cause gastrointestinal irritation or ulceration. May cause burns of the mouth and throat.
 Dermal: Category 3. Toxic in contact with skin.
 Inhalation: Category 2. Fatal if inhaled. Product may give off vapor/fume/aerosol/mist that is very irritating or corrosive to the respiratory system. Exposure to decomposition products can cause serious health hazard. Serious effects may be delayed following exposure.

SKIN CORROSION / IRRITATION: Category 1A. Causes severe skin burns. Effects may be immediate. May cause persistent irritation or dermatitis, redness and blistering.

SERIOUS EYE DAMAGE / IRRITATION: Category 1. Causes serious eye damage. May cause blurred vision. May cause corneal damage resulting in vision impairment or even blindness.

RESPIRATORY SENSITIZATION: Not classified. Based on available data does not meet classification criteria.

SKIN SENSITIZATION: Category 1. May cause allergic skin reaction.

REPRODUCTIVE TOXICITY: Not classified. Based on available data does not meet classification criteria.

MUTAGENICITY: Not classified. Based on available data does not meet classification criteria.

CARCINOGENICITY: Category 2. Suspected of causing cancer.

A component in this product, 4-Methyleimidazole, present at less than 1.0%, is suspected of causing cancer and is listed by IARC as a Group 2B carcinogen. Under the conditions of 2-year NTP feed studies, there was no evidence of carcinogenic activity of 4-Methylimidazole in male rats exposed to 625, 1,250 and 2,500 ppm. There was equivocal evidence of carcinogenic activity of 4-Methylimidazole in female rats based on increased incidences of mononuclear cell leukemia. There was clear evidence of carcinogenic activity of 4-Methylimidazole in male and female mice based on increased incidences of alveolar/bronchiolar neoplasms.

SPECIFIC TARGET ORGAN TOXICITY (Single Exposure): Not classified. Based on available data does not meet classification criteria.

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure): Not classified. Based on available data does not meet classification criteria.

ASPIRATION HAZARD: Not classified. Based on available data does not meet classification criteria.

OTHER HEALTH HAZARD INFORMATON: This product is corrosive to skin and mucous membrane tissues. As a result of this identified hazard, it is anticipated that excessive inhalation of vapors/fumes/mist/aerosol/dust may also corrosive to the respiratory tract.

12. ECOLOGICAL INFORMATION

ACUTE AQUATIC TOXICITY:..... No specific test data available for the mixture. Calculated Estimate: Aquatic Acute Category 2. Toxic to aquatic life. Avoid release to the environment.

CHRONIC AQUATIC TOXICITY: No specific test data available for the mixture. Calculated Estimate: Aquatic Chronic Category 2. Toxic to aquatic life with long lasting effects. Avoid release to the environment.

PERSISTENCE AND BIODEGRADABILITY: No specific test data available for the mixture.

MOBILITY IN SOIL: No specific test data available for the mixture.

ADDITIONAL ECOTOXICITY INFORMATION:..... In the uncured state this product may be harmful to aquatic life with long lasting effects. Prevent release to the environment, sewers and natural waters.

Ingredient	CAS#	Ecotoxicity Classification Information
2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)	6864-37-5	Acute Aquatic Cat. 2; Chronic Aquatic Cat. 2
Isophoronediamine	2855-13-2	Acute Aquatic Cat. 3; Chronic Aquatic Cat. 3
2-ethyl-4-methylimidazole	931-36-2	Acute Aquatic Cat. 3; Chronic Aquatic Cat. 3
4-Methylimidazole	822-36-6	Not classified

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:..... Evaluation of this product using RCRA criteria shows that it is not a hazardous waste, either by listing or characteristics, in its purchased form. It is the responsibility of the user to determine proper disposal methods.

Incinerate, recycle (fuel blending) or reclaim may be preferred methods when conducted in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

US DOT

UN NUMBER: UN 2922
 SHIPPING NAME:..... Corrosive, liquids, toxic, n.o.s.
 TECHNICAL SHIPPING NAME:..... 2,2'-Dimethyl-4,4'-methylenebis (cyclohexylamine)
 HAZARD CLASS:..... Class 8 (6.1)
 PACKING GROUP:..... PG II
 MARINE POLLUTANT: No

CANADA TDG

UN NUMBER: UN 2922
 SHIPPING NAME:..... Corrosive, liquids, toxic, n.o.s.
 TECHNICAL SHIPPING NAME:..... 2,2'-Dimethyl-4,4'-methylenebis (cyclohexylamine)
 HAZARD CLASS:..... Class 8 (6.1)
 PACKING GROUP:..... PG II
 MARINE POLLUTANT: No

IMDG

UN NUMBER: UN 2922
 SHIPPING NAME:..... Corrosive, liquids, toxic, n.o.s.
 TECHNICAL SHIPPING NAME:..... 2,2'-Dimethyl-4,4'-methylenebis (cyclohexylamine)
 HAZARD CLASS:..... Class 8 (6.1)
 PACKING GROUP:..... PG II
 EmS Number: F-A, S-B
 MARINE POLLUTANT Yes

ICAO/IATA

UN NUMBER: UN 2922
 SHIPPING NAME:..... Corrosive, liquids, toxic, n.o.s.
 TECHNICAL SHIPPING NAME:..... 2,2'-Dimethyl-4,4'-methylenebis (cyclohexylamine)
 HAZARD CLASS:..... Class 8 (6.1)
 PACKING GROUP:..... PG II
 MARINE POLLUTANT: Yes

15. REGULATORY INFORMATION

COUNTRY	INVENTORY LIST	STATUS
United States	TSCA	All ingredients are listed or otherwise compliant.
Europe	EINECS or ELINCS	All ingredients are listed or otherwise compliant.
Canada	CEPA (DSL/NDSL)	All ingredients are listed or otherwise compliant.
Australia	AICS	All ingredients are listed or otherwise compliant.
Japan	ENCS	All ingredients are listed or otherwise compliant.

PRO-SET® LAM-251-HT Hardener

South Korea	KECI	All ingredients are listed or otherwise compliant.
China	IECSC	All ingredients are listed or otherwise compliant.
Philippines	PICCS	All ingredients are listed or otherwise compliant.

US EPA TSCA Requirements:
None known.

Canada WHMIS Confidential Business Information (CBI):..... The HMIRA number issued for this CBI claim is #10410. The date of filing is 2016-09-23.

US EPA SARA TITLE III Reporting and Notification Requirements:

- Subject to Section 302 (TPQ)..... No data available.
- Subject to Section 304 (RQ)..... No data available.
- Subject to Section 311 or 312 Acute, Chronic.
- Subject to Section 313 No data available.

US STATE REGULATORY INFORMATION:

The following chemicals may be specifically regulated by individual states. For details on state regulatory requirements you should contact the appropriate state agency.

COMPONENT NAME

CAS NUMBER
4-Methylimidazole
822-36-6

STATE CODE

¹CA, PA, NJ

¹: These substances are known to the state of California to cause cancer or reproductive harm, or both.

16. OTHER INFORMATION


REASON FOR ISSUE:..... Compliant to the requirements of the US OSHA 1910.1200 HazCom 2012 standard. Updates to Sections 3 and 15 to comply with Canada WHMIS 2015 requirements.
PREPARED BY:..... G. M. House
APPROVED BY:..... G. M. House
SDS CONTACT:..... safety@gougeon.com
TITLE:..... Health, Safety & Environmental Manager
APPROVAL DATE:..... October 6, 2016
SUPERSEDES DATE:..... June 1, 2015
SDS VERSION:..... LAM-251-HT-2016a.

OTHER HAZARD INFORMATION AND RATING SYSTEMS:

HMIS® RATING

HEALTH:	3
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:
0 = Low or None; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

Information in this document is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Gougeon Brothers, Inc. The data on this sheet is related only to the specific material designated herein. Gougeon Brothers, Inc. assumes no legal responsibility for use or reliance upon these data.