

# SAFETY DATA SHEET

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:**..... PRO-SET® TLG-625-H Hardener  
**APPLICABLE PRODUCT CODES:** ..... TLG-625-H, TLG-625-H-1, TLG-625-H-2, TLG-625-H-4  
**CHEMICAL FAMILY:**..... Polyamine mixture.  
**INTENDED PRODUCT USES:**..... Curing agent for epoxy resins.  
**PRODUCT RESTRICTIONS:** ..... None identified.  
**SDS VERSION:** ..... TLG-625-H-2016a

**MANUFACTURER:**  
Gougeon Brothers, Inc.  
100 Patterson Ave.  
Bay City, MI 48706, U.S.A.  
Phone: 888-377-6738 or 989-684-7286  
www.prosetepoxy.com

**EMERGENCY TELEPHONE NUMBERS (24 HRS):**  
Transportation  
CHEMTREC: ..... 800-424-9300 (U.S.)  
703-527-3887 (International)  
Non-transportation  
Poison Hotline: 800-222-1222

## 2. HAZARDS IDENTIFICATION

### Classification of Substance or Mixture

Acute toxicity – Inhalation, Category 4  
Skin corrosion/irritation, Category 1C  
Skin sensitizer, Category 1  
Eye damage/irritation, Category 1  
Acute aquatic toxicity, Category 2  
Chronic aquatic toxicity, Category 2

### Label Elements

#### Hazard Pictogram(s):



**Signal Word:**  
DANGER

**Hazard Statements:**  
H332 Harmful if inhaled  
H314 Causes severe skin burns and eye damage  
H317 May cause an allergic skin reaction  
H411 Toxic to aquatic life with long lasting effects

#### **Precautionary Statements:**

##### Prevention

P260 Do not breathe dusts/fumes/gas/mists/vapors/spray  
P264 Wash hands thoroughly after handling  
P271 Use only outdoors or in a well ventilated area  
P272 Contaminated work clothing should not be allowed out of the workplace  
P273 Avoid release to the environment  
P280 Wear protective gloves/protective clothing/eye protection/face protection

##### Response

P301 + P330 + 331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse or wash skin with soap and water (or shower).  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CONTROL CENTER or doctor  
P333 + P313 If skin irritation or rash occurs: Get medical attention/advice  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P391 Collect spillage

##### Storage

P405 Store locked up.

##### Disposal

P501 Dispose of contents and container according to local, state, national and International regulations

### Other Hazards

# PRO-SET® TLG-625-H HARDENER

None known.

## 3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT NAME	CAS #	CONCENTRATION (%)
Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	68082-29-1	30-70
Benzyl alcohol	100-51-6	10-30
Soda lime borosilicate glass	65997-17-3	10-30
Benzene-1,3-dimethanamine, reaction products with phenol and formaldehyde	57214-10-5	10-30
Benzene-1,3-dimethanamine	1477-55-0	1-10
Synthetic amorphous, pyrogenic silica	112945-52-5	1-10
Triethylenetetramine	112-24-3	1-5
Polymer of epichlorohydrin / bisphenol A and diethylenetriamine	31326-29-1	1-5

The exact chemical identity and/or exact percentage (concentration) of each ingredient may be held as a trade secret. Ingredient ranges provided may represent actual concentration ranges. Any ingredient not disclosed may have been determined not to pose a health or environmental hazard, or may only be present in concentrations that do not require disclosure. Refer to Section 15 for additional information regarding a WHMIS CBI claim.

## 4. FIRST AID MEASURES

**FIRST AID FOR EYES**..... SYMPTOMS: Causes eye burns and eye damage. RESPONSE: Flush immediately with water for at least 15 minutes. Remove contact lenses if present and easy to do. Immediately call a POISON CONTROL CENTER or doctor.

**FIRST AID FOR SKIN**..... SYMPTOMS: Causes skin burns, redness and irritation. May cause allergic skin reaction and sensitization. RESPONSE: Immediately wash skin with soap and water. Immediately call a POISON CONTROL CENTER or doctor.

**FIRST AID FOR INHALATION**..... SYMPTOMS: Can cause respiratory irritation, shortness of breath or cough. RESPONSE: Remove to fresh air if effects occur and keep comfortable for breathing. Immediately call a physician/doctor if symptoms develop and persist or if you feel unwell.

**FIRST AID FOR INGESTION**..... SYMPTOMS: May cause gastrointestinal irritation or ulceration. May cause burns of the mouth and throat. RESPONSE: Rinse mouth with water. DO NOT induce vomiting. If vomiting should occur, keep airway clear. Immediately call POISON CONTROL CENTER or doctor.

## 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** ..... SUITABLE: Foam, carbon dioxide (CO<sub>2</sub>), dry chemical. NON-SUITABLE: Direct, high-pressure water stream.

**FIRE AND EXPLOSION HAZARDS:** ..... During a fire, smoke may contain the original materials in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include, but are not limited to: oxides of nitrogen, carbon monoxide, carbon dioxide, volatile amines, ammonia, nitric acid, nitrosamines. When mixed with sawdust, wood chips, or other cellulosic material, spontaneous combustion can occur under certain conditions. Heat is generated as the air oxidizes the amine. If the heat is not dissipated quickly enough, it can ignite the sawdust.

**SPECIAL FIRE FIGHTING PROCEDURES:** ..... Use full-body protective gear and a self-contained breathing apparatus. Use of water may generate toxic aqueous solutions. Do not allow water run-off from fighting fire to enter drains or other water courses.

## 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS AND PROTECTIVE EQUIPMENT:** ..... Keep unnecessary and unprotected personnel from entering area. Use appropriate safety and personal protective equipment as indicated in Section 8.

**MITIGATION AND CLEAN UP PROCEDURES:** ..... Stop leak without additional risk. Isolate area. Dike and absorb with inert material (e.g., sand) and collect in a suitable, closed container. Do not use sawdust, wood chips or other cellulosic materials to absorb the spill, as the possibility for spontaneous combustion exists. Warm, soapy water may be used to clean residual.

**ENVIRONMENTAL PRECAUTIONS:**..... Prevent from entering into soil, ditches, sewers, waterways and groundwater. See Section 12 for environmental impact information.

## 7. HANDLING AND STORAGE

# PRO-SET® TLG-625-H HARDENER

**STORAGE TEMPERATURE (min./max.):** ..... 40°F (4°C) / 90°F (32°C).

**STORAGE:** ..... Store in cool, dry place away from high temperatures and moisture. Keep container tightly closed. Store in a secure location with restricted access or store locked up.

**HANDLING PRECAUTIONS:** ..... Use only with adequate ventilation. Do not breathe vapors or mists from heated material. Avoid exposure to concentrated vapors. Avoid skin and eye contact. Wash thoroughly after handling. When mixed with epoxy resin this product causes an exothermic reaction, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapors that vary widely in composition and toxicity.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**EYE PROTECTION GUIDELINES:** ..... Chemical splash-proof goggles or face shield.

**SKIN PROTECTION GUIDELINES:** ..... Wear liquid-proof, chemical resistant gloves (nitrile-butyl rubber, neoprene, butyl rubber or natural rubber) and full body-covering clothing.

**RESPIRATORY/VENTILATION GUIDELINES:** ..... Use with adequate general ventilation and/or local ventilation to keep exposures below established limits. When ventilation cannot be made adequate enough to keep exposures below established limits, use a NIOSH approved respirator with an organic vapor cartridge, organic vapor cartridge + P100, or a multi-contaminant cartridge, depending on specific workplace conditions. Consult with your respirator and cartridge supplier to ensure proper selection of respirator and cartridge based on ingredients listed in Section 3 and specific workplace conditions. Use and select a respirator according to the guidelines established in OSHA 1910.134 or other applicable respiratory protection standard.

**ADDITIONAL PROTECTIVE MEASURES:** ..... Use where there is immediate access to safety shower and emergency eye wash. Wash thoroughly after use. Contact lens should not be worn when working with this material. Generally speaking, working cleanly and following basic precautionary measures will greatly minimize the potential for harmful exposure to this product under normal use conditions.

**OCCUPATIONAL EXPOSURE LIMITS:** ..... Exposure limits may not be established for this product as a whole. For established exposure limits of specific ingredients in this product, or other available exposure limit information, refer to the table below.

Ingredient Name	CAS#	Exposure Limit Information
Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	68082-29-1	No data available (reference triethylenetetramine)
Benzyl alcohol	100-51-6	10 ppm TWA (WEEL)
Soda lime borosilicate glass	65997-17-3	Dust and PNOS: ACGIH 10mg/m <sup>3</sup> , TWA, Inhalable; 3 mg/m <sup>3</sup> , TWA, Respirable; OSHA PEL 15 mg/m <sup>3</sup> , TWA, total dust; 5 mg/m <sup>3</sup> , TWA, Respirable
Benzene-1,3-dimethanamine, reaction products with phenol and formaldehyde	57214-10-5	No data available
Benzene-1,3-dimethanamine	1477-55-0	NIOSH CEILING: 0.1 mg/m <sup>3</sup> ; Remarks: Potential for dermal absorption. ACGIH TLV CEILING: 0.1 mg/m <sup>3</sup> ; SKIN OSHA CEILING: 0.1 mg/m <sup>3</sup> ; Table Z 1A
Synthetic amorphous, pyrogenic silica	112945-52-5	Amorphous silica: OSHA PEL 6 mg/m <sup>3</sup>  Dust and PNOS: ACGIH 10mg/m <sup>3</sup> , TWA, Inhalable; 3 mg/m <sup>3</sup> , TWA, Respirable; OSHA PEL 15 mg/m <sup>3</sup> , TWA, total dust; 5 mg/m <sup>3</sup> , TWA, Respirable
Triethylenetetramine	112-24-3	AIHA WEEL: 1 ppm ; 6 mg/m <sup>3</sup> ; SKIN
Polymer of epichlorohydrin / bisphenol A and diethylenetriamine	31326-29-1	No data available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL FORM:** ..... Paste.  
**COLOR:** ..... Light brown.  
**ODOR:** ..... Ammonia-like  
**ODOR THRESHOLD:** ..... No data available  
**pH:** ..... No data. Estimated to be between 10-12.5 based on ingredient data.  
**MELTING POINT / FREEZING POINT** ..... No data.  
**BOILING POINT (760mm/Hg):** ..... > 400°F (204°C) estimated based on similar product.  
**FLASH POINT:** ..... Estimated > 200°F (93°C) estimated based similar product.  
**AUTO IGNITION TEMPERATURE** ..... No data.  
**LOWER EXPLOSIVE LIMIT (LEL)** ..... No data.  
**UPPER EXPLOSIVE LIMIT (UEL)** ..... No data.  
**VAPOR PRESSURE** ..... < 1 mmHg @ 20°C (estimated based on ingredient data).  
**SPECIFIC GRAVITY/DENSITY (water = 1)** ..... 0.49

# PRO-SET® TLG-625-H HARDENER

**BULK DENSITY**..... 4.09 lbs./gal. (0.49 kg/L)  
**VAPOR DENSITY (air = 1)** ..... No data.  
**EVAPORATION RATE (Butyl Acetate = 1)**..... No data.  
**WATER SOLUBILITY (% BY WT.)** ..... No data.  
**PARTITION COEFFICIENT, n-OCTANOL/WATER (log Pow)**..... No data.  
**KINEMATIC VISCOSITY:** ..... Paste. (mm<sup>2</sup>/s @ 20°C)  
**DECOMPOSITION TEMPERATURE:** ..... No data available.  
**% VOLATILE BY WEIGHT:** ..... ASTM 2369-07 was used to determine the Volatile Matter Content of mixed epoxy resin and hardener. The combined VOC content for the resin and hardener system is listed below.

Resin/Hardener	VOC Content	
	(g/L)	(lb/gal)
TLG-625-R / TLG-625-H	3.77	0.03

## 10. STABILITY AND REACTIVITY

**STABILITY:** ..... Product is stable at normal temperatures and pressures.  
**REACTIVITY/HAZARDOUS REACTIONS:** ..... Product will not react by itself. A mass of more than one pound of product plus an epoxy resin will cause irreversible polymerization with significant heat buildup and pressure.  
**INCOMPATIBILITIES:** ..... Avoid acids, oxidizing materials, halogenated organic compounds (e.g., methylene chloride). External heating or self-heating could result in rapid temperature increase and pressure build up. If such a condition were to occur in a drum, the drum could expand and rupture violently.  
**CONDITIONS TO AVOID:** ..... Avoid excessive heat.  
**DECOMPOSITION PRODUCTS:** ..... Very toxic fumes and gases when burned or otherwise heated to decomposition. Decomposition products may include, but not limited to: oxides of nitrogen, volatile amines, ammonia, nitric acid, nitrosamines.

## 11. TOXICOLOGICAL INFORMATION

Ingredient Name	CAS#	LD <sub>50</sub> Oral	LD <sub>50</sub> Dermal	LC <sub>50</sub> Inhalation
Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	68082-29-1	No data available (reference triethylenetetramine)	No data available (reference triethylenetetramine)	No data available (reference triethylenetetramine)
Benzyl alcohol	100-51-6	1620 mg/kg	No data available	>4.18 mg/l 4h aerosol
Soda lime borosilicate glass	65997-17-3	No data available	No data available	No data available
Benzene-1,3-dimethanamine, reaction products with phenol and formaldehyde	57214-10-5	No data available	No data available	No data available
Benzene-1,3-dimethanamine	1477-55-0	980 mg/kg	2000 mg/kg	1.34 mg/l 4h dust/mist
Synthetic amorphous, pyrogenic silica	112945-52-5	>5000 mg/kg	>2000 mg/kg	No data available
Triethylenetetramine	112-24-3	1716.2 mg/kg	805 mg/kg	No data
Polymer of epichlorohydrin / bisphenol A and diethylenetriamine	31326-29-1	1620 mg/kg	No data available	No data available

**ACUTE TOXICITY:** ..... No specific toxicity data exists for this mixture. Classification is based on acute toxicity estimation methods using ingredient data.  
 Oral: ..... Not classified. Based on available data this product does not meet classification criteria.  
 Dermal: ..... Not classified. Based on available data this product does not meet classification criteria.  
 Inhalation: ..... Category 4. Harmful if inhaled. Can cause respiratory irritation, shortness of breath or cough.  
**SKIN CORROSION / IRRITATION:** ..... Category 1C. Causes severe skin burns. Effects may be immediate. May cause persistent irritation or dermatitis.  
**SERIOUS EYE DAMAGE / IRRITATION:** ..... Category 1. Causes serious eye damage. May cause blurred vision. May cause corneal damage resulting in vision impairment or even blindness.  
**RESPIRATORY SENSITIZATION:** ..... Not classified. Based on available data this product does not meet classification criteria.  
**SKIN SENSITIZATION:** ..... Category 1. May cause allergic skin reaction.

**PRO-SET® TLG-625-H HARDENER**

**REPRODUCTIVE TOXICITY:**..... Not classified. Based on available data this product does not meet classification criteria.

**MUTAGENICITY:**..... Not classified. Based on available data this product does not meet classification criteria.

**CARCINOGENICITY:**..... Not classified. Based on available data this product does not meet classification criteria.

**SPECIFIC TARGET ORGAN TOXICITY (Single Exposure):**..... Not classified. Based on available data this product does not meet classification criteria.

**SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure):** ..... Not classified. Based on available data this product does not meet classification criteria.

**ASPIRATION HAZARD:** ..... Not classified. Based on available data this product does not meet classification criteria.

**OTHER HEALTH HAZARD INFORMATION:**..... None known.

**12. ECOLOGICAL INFORMATION**

**ACUTE AQUATIC TOXICITY:**..... Aquatic Acute Category 2. Calculated Estimate. No specific test data available for the mixture. Toxic to aquatic life. Avoid release to the environment.

**CHRONIC AQUATIC TOXICITY:** ..... Aquatic Chronic Category 2. Calculated Estimate. No specific test data available for the mixture. Toxic to aquatic life with long lasting effects. Avoid release to the environment.

**PERSISTENCE AND BIODEGRADABILITY:** ..... No specific test data available for the mixture.

**MOBILITY IN SOIL:** ..... No specific test data available for the mixture.

**ADDITIONAL ECOTOXICITY INFORMATION:**..... In the liquid, uncured state, this product may be harmful to aquatic life with long lasting effects. Prevent release to the environment, sewers and natural waters.

Ingredient	CAS#	Ecotoxicity Classification Information
Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	68082-29-1	Chronic Aquatic Cat. 2
Benzyl alcohol	100-51-6	No data available
Soda lime borosilicate glass	65997-17-3	Not classified
Benzene-1,3-dimethanamine, reaction products with phenol and formaldehyde	57214-10-5	Acute Aquatic Cat. 1; Chronic Aquatic Cat. 1
Benzene-1,3-dimethanamine	1477-55-0	Acute Aquatic Cat. 3; Chronic Aquatic Cat. 3
Synthetic amorphous, pyrogenic silica	112945-52-5	Not classified
Triethylenetetramine	112-24-3	Chronic Aquatic Cat. 3
Polymer of epichlorohydrin / bisphenol A and diethylenetriamine	31326-29-1	No data available

**13. DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:**..... Evaluation of this product using RCRA criteria shows that it is not a hazardous waste, either by listing or characteristics, in its purchased form. It is the responsibility of the user to determine proper disposal methods.

Incinerate, recycle (fuel blending) or reclaim may be preferred methods when conducted in accordance with federal, state and local regulations.

**14. TRANSPORTATION INFORMATION**

**US DOT**

UN NUMBER: ..... UN 3259  
 SHIPPING NAME:..... Polyamines, solid, corrosive, n.o.s.  
 TECHNICAL SHIPPING NAME: ..... Benzene-1,3-dimethanamine  
 HAZARD CLASS:..... Class 8  
 PACKING GROUP:..... PG III  
 MARINE POLLUTANT: ..... No

**CANADA TDG**

UN NUMBER: ..... UN 3259  
 SHIPPING NAME:..... Polyamines, solid, corrosive, n.o.s.  
 TECHNICAL SHIPPING NAME: ..... Benzene-1,3-dimethanamine  
 HAZARD CLASS:..... Class 8  
 PACKING GROUP:..... PG III

# PRO-SET® TLG-625-H HARDENER

MARINE POLLUTANT: ..... No

**IMDG**

UN NUMBER: ..... UN 3259  
 SHIPPING NAME: ..... Polyamines, solid, corrosive, n.o.s.  
 TECHNICAL SHIPPING NAME: ..... Benzene-1,3-dimethanamine  
 HAZARD CLASS: ..... Class 8  
 PACKING GROUP: ..... PG III  
 EmS Number: ..... F-A, S-B  
 MARINE POLLUTANT ..... Yes

**ICAO/IATA**

UN NUMBER: ..... UN 3259  
 SHIPPING NAME: ..... Polyamines, solid, corrosive, n.o.s.  
 TECHNICAL SHIPPING NAME: ..... Benzene-1,3-dimethanamine  
 HAZARD CLASS: ..... Class 8  
 PACKING GROUP: ..... PG III  
 MARINE POLLUTANT: ..... Yes

**15. REGULATORY INFORMATION**

COUNTRY	INVENTORY LIST	STATUS
United States	TSCA	All ingredients are listed or otherwise compliant.
Europe	EINECS or ELINCS	All ingredients are listed or otherwise compliant.
Canada	CEPA (DSL/NDL)	All ingredients are listed or otherwise compliant.
Australia	AICS	All ingredients are listed or otherwise compliant.
Japan	ENCS	All ingredients are listed or otherwise compliant.
South Korea	KECI	All ingredients are listed or otherwise compliant.
China	IECSC	All ingredients are listed or otherwise compliant.
Philippines	PICCS	All ingredients are listed or otherwise compliant.

**US EPA TSCA Requirements:**..... No data available.

**Canada WHMIS Confidential Business Information (CBI):**..... The HMIRA number issued for this CBI claim is #10428. The date of filing is 2016-10-07.

**US EPA SARA TITLE III Reporting and Notification Requirements:**

Subject to Section 302 (TPQ)..... No data available.  
 Subject to Section 304 (RQ)..... No data available.  
 Subject to Section 311 or 312 ..... No data available.  
 Subject to Section 313 ..... No data available.

**US STATE REGULATORY INFORMATION:**

The following chemicals may be specifically regulated by individual states. For details on state regulatory requirements you should contact the appropriate state agency.

**COMPONENT NAME**

<u>CAS NUMBER</u>	<u>CONCENTRATION</u>	<u>STATE CODE</u>
Benzene-1,3-dimethanamine 1477-55-0		MA, PA, NJ
Amorphous silica 7631-86-9 or 112945-52-5		PA, NJ, MA
Triethylenetetramine 112-14-3		PA, MA, NJ

<sup>1</sup>: These substances are known to the state of California to cause cancer or reproductive harm, or both.

**16. OTHER INFORMATION**

**REASON FOR ISSUE:**..... Compliant to the requirements of the US OSHA 1910.1200 HazCom 2012 standard. Updates to Sections 3 and 15 to comply with Canada WHMIS 2015 requirements.

**PREPARED BY:**..... G. House  
**APPROVED BY:**..... G. House  
**TITLE:** ..... Health, Safety & Environmental Manager  
**APPROVAL DATE:** ..... October 11, 2016  
**SUPERSEDES DATE:** ..... June 1, 2015  
**SDS VERSION:** ..... TLG-625-H-2016a

**OTHER HAZARD INFORMATION AND RATING SYSTEMS:**


**HMIS® RATING**

**NFPA® 704 CODES**

# PRO-SET® TLG-625-H HARDENER

---

<b>HEALTH:</b>	<b>3</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	



*Approximate HMIS and NFPA Risk Ratings Legend:*  
0 = Low or None; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

Information in this document is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Gougeon Brothers, Inc. The data on this sheet is related only to the specific material designated herein. Gougeon Brothers, Inc. assumes no legal responsibility for use or reliance upon these data.