

SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:..... PRO-SET® XR28A Resin
APPLICABLE PRODUCT CODES:XR28A, XR28A-1, XR28A-2, XR28A-4
CHEMICAL FAMILY:..... Epoxy resin mixture.
INTENDED PRODUCT USES:..... Fire retardant resin applications.
PRODUCT RESTRICTIONS:..... Use product only for intended uses as listed. Export restrictions.
SDS VERSION:XR28A-2016a

MANUFACTURER:
Gougeon Brothers, Inc.
100 Patterson Ave.
Bay City, MI 48706, U.S.A.
Phone: 888-377-6738 or 989-684-7286
www.prosetepoxy.com

EMERGENCY TELEPHONE NUMBERS (24 HRS):
Transportation
CHEMTREC: 800-424-9300 (U.S.)
703-527-3887 (International)
Non-transportation
Poison Hotline: 800-222-1222

2. HAZARDS IDENTIFICATION

Classification of Substance or Mixture

Skin corrosion/irritation, Category 2
Skin sensitizer, Category 1
Eye damage/irritation, Category 2A
Germ cell mutagenicity, Category 1B
Reproductive toxicity, Category 2
Chronic aquatic toxicity, Category 2

Label Elements

Hazard Pictogram(s):



Signal Word:
DANGER

Hazard Statements:

H315 Causes skin irritation
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H340 May cause genetic defects
H361 Suspected of damaging fertility or the unborn child
H411 Toxic to aquatic life with long lasting effects

Precautionary Statements:

Prevention

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 If exposed or concerned: Get medical attention/advice.
P333 + P313 If skin irritation or rash occurs: Get medical attention/advice.
P337 + P313 If eye irritation persists: Get medical attention/advice.
P362 + P364 Take off contaminated clothing and wash it before re-use.
P391 Collect spillage.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local, regional and international regulations.

Other Hazards

None known.

3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT NAME	CAS #	CONCENTRATION (%)
Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	25085-99-8	60-100
Oxirane, 2,2'[(2,2-dimethyl-1,3-propanediyl)bis(oxymethylene)]bis-	17557-23-2	10-30
Dimethyl methylphosphonate	756-79-6	1-10

The exact chemical identity and/or exact percentage (concentration) of each ingredient has been held as confidential business information (CBI). Refer to Section 15 for additional information regarding this CBI claim.

4. FIRST AID MEASURES

FIRST AID FOR EYES:..... SYMPTOMS: Causes serious irritation and redness. RESPONSE: Flush immediately with water for at least 15 minutes. Remove contact lenses if present and easy to do. Consult a physician as precautionary measure.

FIRST AID FOR SKIN:..... SYMPTOMS: Causes skin irritation. May cause allergic skin reaction and sensitization. RESPONSE: Remove contaminated clothing. Wipe excess from skin. Apply waterless skin cleaner and then wash with soap and water. Consult a physician if effects occur.

FIRST AID FOR INHALATION:..... SYMPTOMS: Not a likely route of exposure under normal conditions of use. RESPONSE: Remove to fresh air if respiratory irritation occurs and keep comfortable for breathing.

FIRST AID FOR INGESTION:..... SYMPTOMS: No acute adverse health effects expected from amounts ingested under normal conditions of use. RESPONSE: Seek medical advice.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:..... SUITABLE: Foam, carbon dioxide (CO₂), dry chemical. NON-SUITABLE: Direct water stream.

FIRE AND EXPLOSION HAZARDS:..... During a fire, smoke may contain the original materials in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include, but are not limited to: phenolics, carbon oxides, phosphorous oxides.

SPECIAL FIRE FIGHTING PROCEDURES:..... Wear a self-contained breathing apparatus and complete full-body personal protective equipment. Closed containers may rupture (due to buildup of pressure) when exposed to extreme heat.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS AND PROTECTIVE EQUIPMENT:..... Keep unnecessary and unprotected personnel from entering area. Use appropriate safety and personal protective equipment as indicated in Section 8.

MITIGATION AND CLEAN UP PROCEDURES:..... Stop leak without additional risk. Isolate area. Dike and absorb with inert material (e.g., sand) and collect in a suitable, closed container. Warm, soapy water or non-flammable, safe solvent may be used to clean residual.

ENVIRONMENTAL PRECAUTIONS:..... Prevent from entering into soil, ditches, sewers, waterways and groundwater. See Section 12 for environmental impact information.

7. HANDLING AND STORAGE

STORAGE TEMPERATURE (min./max.):..... 40°F (4°C) / 120°F (49°C)

STORAGE:..... Store in cool, dry place. Store in tightly sealed containers to prevent moisture absorption and loss of volatiles. Excessive heat over long periods of time will degrade the resin.

HANDLING PRECAUTIONS:..... Avoid all skin and eye contact. Wash thoroughly after handling. Launder contaminated clothing before reuse. Avoid inhalation of vapors from heated product. Precautionary steps should be taken when curing product in large quantities. When mixed with epoxy curing agents this product causes an exothermic, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapors that vary widely in composition and toxicity.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION GUIDELINES:..... Safety glasses with side shields or chemical splash goggles.

SKIN PROTECTION GUIDELINES:..... Wear liquid-proof, chemical resistant gloves (nitrile-butyl rubber, neoprene, butyl rubber or natural rubber) and full body-covering clothing.

RESPIRATORY/VENTILATION GUIDELINES:..... Use with adequate general ventilation and/or local ventilation to keep exposures below established limits. When ventilation cannot be made adequate enough to keep exposures below established limits, use a NIOSH approved respirator with an organic vapor cartridge, or organic vapor cartridge + P100 particulate filter, depending on specific workplace conditions. Consult with your respirator and cartridge supplier to ensure proper selection of respirator and cartridge based on ingredients listed in Section 3 and specific workplace conditions. Use and select a respirator according the guidelines established in OSHA 1910.134 or other applicable respiratory protection standard.

ADDITIONAL PROTECTIVE MEASURES:..... Practice good caution and personal cleanliness to avoid skin and eye contact. Avoid skin contact when removing gloves and other protective equipment. Wash thoroughly after handling. Generally speaking, working cleanly and following basic precautionary measures will greatly minimize the potential for harmful exposure to this product under normal use conditions.

OCCUPATIONAL EXPOSURE LIMITS:..... Exposure limits may not be established for this product as a whole. For established exposure limits of specific ingredients in this product, or other available exposure limit information, refer to the table below.

Ingredient Name	CAS#	Exposure Limit Information
Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	25085-99-8	No data available.
Oxirane, 2,2'[(2,2-dimethyl-1,3-propanediyl)bis(oxymethylene)]bis-Dimethyl methylphosphonate	17557-23-2	No data available.
	756-79-6	No data available.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM:..... Viscous liquid.
COLOR:..... Colorless.
ODOR:..... Mild.
ODOR THRESHOLD:..... No data available
pH:..... No data available
MELTING POINT / FREEZING POINT..... No data available
BOILING POINT (760mm/Hg):..... >400°F (204°C) Estimated based on ingredient data.
FLASH POINT:..... >200°F (93°C) Based on ASTM D92 test results from similar product.
AUTO IGNITION TEMPERATURE..... No data available
LOWER EXPLOSIVE LIMIT (LEL)..... No data available
UPPER EXPLOSIVE LIMIT (UEL)..... No data available
VAPOR PRESSURE..... No data available
SPECIFIC GRAVITY/DENSITY (water = 1)..... 1.14
BULK DENSITY..... 9.49 lbs./gal. (1.14 kg/L)
VAPOR DENSITY (air = 1)..... < 1 mmHg@ 20°C. Estimated based on ingredient data.
EVAPORATION RATE (Butyl Acetate = 1)..... No data available
WATER SOLUBILITY (% BY WT.)..... No data available
PARTITION COEFFICIENT, n-OCTANOL/WATER (log Pow)..... No data available
KINEMATIC VISCOSITY:..... 478 mm²/s @ 20°C
DECOMPOSITION TEMPERATURE:..... No data available.
% VOLATILE BY WEIGHT:..... ASTM D 2369-07 was used to determine the Volatile Content of mixed epoxy resin and hardener. Refer to the hardener SDS for information about the total volatile content of the resin/hardener system.

10. STABILITY AND REACTIVITY

STABILITY:..... Product is stable at normal temperatures and pressures.
REACTIVITY/HAZARDOUS REACTIONS:..... Product will not react by itself. A mass of more than one pound of product plus an aliphatic amine will cause irreversible polymerization with significant heat buildup. Strong acids, bases, amines and mercaptans can cause polymerization.
INCOMPATIBILITIES:..... Strong acids, bases, amines and mercaptans can cause polymerization. External heating or self-heating could result in rapid temperature increase and pressure buildup. If such a condition were to occur in a drum, the drum could expand and rupture violently.
CONDITIONS TO AVOID:..... Avoid excessive heat.
DECOMPOSITION PRODUCTS:..... Carbon oxides, phosphorous oxides and phenolics may be produced during uncontrolled exothermic reactions or when otherwise heated to decomposition.

11. TOXICOLOGICAL AND HAZARD ENDPOINT INFORMATION

Component Name	CAS#	LD ₅₀ Oral	LD ₅₀ Dermal	LC ₅₀ Inhalation
Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	25085-99-8	>15,000 mg/kg (rat)	>23,000 mg/kg (rabbit)	No data
Oxirane, 2,2'[(2,2-dimethyl-1,3-propanediyl)bis(oxymethylene)]bis-	17557-23-2	4500 mg/kg	>2000 mg/kg	No data
Dimethyl methylphosphonate	756-79-6	>5000 mg/kg	4640 mg/kg	>2.59 mg/l 4h

ACUTE TOXICITY: No specific toxicity data exists for this mixture. Classification is based on acute toxicity estimation methods using ingredient data.
 Oral: Not classified. Does not meet acute oral toxicity criteria.
 Dermal: Not classified. Does not meet acute dermal toxicity criteria.
 Inhalation: Not classified. Does not meet acute inhalation toxicity criteria. If product is heated, vapors generated can cause headache, nausea, dizziness and possible respiratory irritation if inhaled in high concentrations.

SKIN CORROSION / IRRITATION: Causes skin irritation – Category 2.

SERIOUS EYE DAMAGE / IRRITATION: Causes serious eye irritation. Category 2A.

RESPIRATORY SENSITIZATION: Not classified. Does not meet criteria for respiratory sensitizer. Repeated exposure to high vapor concentrations may cause irritation of pre-existing lung allergies and increase the chance of developing allergy symptoms to this product.

SKIN SENSITIZATION: May cause allergic skin reaction. Category 1.

REPRODUCTIVE TOXICITY: Suspected of damaging fertility or the unborn child. Category 2.

Diglycidyl ether bisphenol-A, in animal studies, has been shown not to interfere with reproduction. Diglycidyl ether bisphenol-A did not cause birth defects or other adverse effects on the fetus when pregnant rabbits were exposed by skin contact, the most likely route of exposure, or when pregnant rats or rabbits were exposed orally.

Dimethyle methylphosphonate has been shown to cause impairment of fertility in laboratory animal studies. Suspected human reproductive toxicant. Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count). Effects on Fertility: Male fertility index (Ex. number of males impregnating females per number of males exposed to fertile non-pregnant females).

MUTAGENICITY: May cause genetic defects. Category 1B.

Dimethyl methylphosphonate showed mutagenic effects in in vivo testing. The substance was not mutagenic in bacteria. The substance was mutagenic in a mammalian cell culture test system. The substance was mutagenic in studies with mammals.

Diglycidyl ether bisphenol-A in animal mutagenicity studies were negative. In vitro mutagenicity tests were negative in some cases and positive in others.

CARCINOGENICITY: Not classified. Does not meet criteria for carcinogenicity.

Many studies have been conducted to assess the potential carcinogenicity of diglycidyl ether of bisphenol-A. Although some weak evidence of carcinogenicity has been reported in animals, when all of the data are considered, the weight of evidence does not show that Diglycidyl ether bisphenol-A is carcinogenic. Indeed, the most recent review of the available data by the International Agency for Research on Cancer (IARC) has concluded that Diglycidyl ether bisphenol-A is not classified as a carcinogen.

Epichlorohydrin, an impurity in this product (<5 ppm) has been reported to produce cancer in laboratory animals and to produce mutagenic changes in bacteria and cultured human cells. It has been established by the International Agency for Research on Cancer (IARC) as a probable human carcinogen (Group 2A) based on the following conclusions: human evidence – inadequate; animal evidence – sufficient. It has been classified as an anticipated human carcinogen by the National Toxicology Program (NTP). Note: It is unlikely that normal use of this product would result in measurable exposure concentrations to this substance.

SPECIFIC TARGET ORGAN TOXICITY (Single Exposure): Not classified. Does not meet STOT SE criteria.

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure): Not classified. Does not meet STOT RE criteria.

ASPIRATION HAZARD: Not classified. Does not meet aspiration toxicity criteria.

OTHER HEALTH HAZARD INFORMATION: Excessive inhalation of a high concentration of vapors may cause slight respiratory irritation.

12. ECOLOGICAL INFORMATION

ACUTE AQUATIC TOXICITY: No specific test data available for the mixture. Calculated Estimate: Does not meet acute aquatic toxicity requirements.

CHRONIC AQUATIC TOXICITY: No specific test data available for the mixture. Calculated Estimate: Aquatic Chronic Category 2.

PERSISTENCE AND BIODEGRADABILITY: No specific test data available for the mixture.

MOBILITY IN SOIL: No specific test data available for the mixture.

ADDITIONAL ECOTOXICITY INFORMATION: In the liquid, uncured state, this product may be harmful to aquatic life long lasting effects. Prevent release to the environment, sewers and natural waters.

Ingredient	CAS#	Ecotoxicity Classification Information
------------	------	--

Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	25085-99-8	Aquatic Chronic Cat. 2
Oxirane, 2,2'[(2,2-dimethyl-1,3-propanediyl)bis(oxymethylene)]bis-	17557-23-2	Not classified.
Dimethyl methylphosphonate	756-79-6	Not classified.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:..... Evaluation of this product using RCRA criteria shows that it is not a hazardous waste, either by listing or characteristics, in its purchased form. It is the responsibility of the user to determine proper disposal methods.

Incinerate, recycle (fuel blending) or reclaim may be preferred methods when conducted in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

US DOT

UN NUMBER: Not regulated.
 SHIPPING NAME:..... Not applicable.
 TECHNICAL SHIPPING NAME:..... Not applicable.
 HAZARD CLASS:..... Not applicable.
 PACKING GROUP:..... Not applicable.

CANADA TDG

UN NUMBER: Not regulated.
 SHIPPING NAME:..... Not applicable.
 TECHNICAL SHIPPING NAME:..... Not applicable.
 HAZARD CLASS:..... Not applicable.
 PACKING GROUP:..... Not applicable.

ICAO/IATA

UN NUMBER: UN 3082.
 SHIPPING NAME:..... Environmentally hazardous substance, liquid, n.o.s.
 TECHNICAL SHIPPING NAME:..... Epoxy Resin.
 HAZARD CLASS:..... Class 9.
 PACKING GROUP:..... PG III.
 MARINE POLLUTANT:..... Yes

IMDG

UN NUMBER: UN 3082.
 SHIPPING NAME:..... Environmentally hazardous substance, liquid, n.o.s.
 TECHNICAL SHIPPING NAME:..... Epoxy Resin.
 HAZARD CLASS:..... Class 9.
 PACKING GROUP:..... PG III.
 EmS Number: F-A, S-F
 MARINE POLLUTANT Yes

15. REGULATORY INFORMATION

COUNTRY	INVENTORY LIST	STATUS
United States	TSCA	All ingredients are listed or otherwise compliant.
Europe	EINECS or ELINCS	All ingredients are listed or otherwise compliant.
Canada	CEPA (DSL/NDL)	All ingredients are listed or otherwise compliant.
Australia	AICS	No data available on CAS# 756-79-6.
Japan	ENCS	No data available on CAS# 756-79-6.
South Korea	KECI	No data available on CAS# 756-79-6.
China	IECSC	No data available on CAS# 756-79-6.
Philippines	PICCS	No data available on CAS# 756-79-6.
New Zealand	NZIoC	No data available on CAS# 756-79-6.

US EPA SARA TITTLE III Reporting and Notification Requirements:

Subject to Section 302 (TPQ) No data available.
 Subject to Section 304 (RQ)..... No data available.
 Subject to Section 311 or 312 Acute, Chronic.
 Subject to Section 313 No data available.

Canada WHMIS Confidential Business Information (CBI):..... The HMIRA number issued for this CBI claim is #10311. The date of filing is 2016-08-09.

STATE REGULATORY INFORMATION:

Chemicals listed below may be specifically regulated by individual states. For details on state regulatory requirements you should contact the appropriate state agency.

COMPONENT NAME
/CAS NUMBER

STATE CODE

PRO-SET® XR28A Resin

Epichlorohydrin 106-89-8	< 5ppm	¹ CA
Dimethyl methylphosphonate 756-79-6		PA, NJ

¹: These substances are known to the state of California to cause cancer or reproductive harm, or both.

16. OTHER INFORMATION


REASON FOR ISSUE:..... Update to Sections 3 and 15 to meet Canada WHMIS 2015 requirements.
 PREPARED BY:..... G. M. House
 APPROVED BY:..... G. M. House
 SDS CONTACT:..... safety@gougeon.com
 TITLE:..... Health, Safety & Environmental Manager
 APPROVAL DATE:..... August 24, 2016
 SUPERSEDES DATE:..... June 1, 2015
 SDS VERSION:..... XR28A-2016a

OTHER HAZARD INFORMATION AND RATING SYSTEMS:

HMIS® RATING

HEALTH:	2
FLAMMABILITY:	1
PHYSICAL HAZARD:	1
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:
 0 = Low or None; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

Information in this document is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Gougeon Brothers, Inc. The data on this sheet is related only to the specific material designated herein. Gougeon Brothers, Inc. assumes no legal responsibility for use or reliance upon these data.